



Heatless Desiccant Dryers 2.5-142 m³/min, 800-5,000 cfm

HL heatless desiccant dryers use twin desiccant towers with strategically positioned valves to dry compressed air. The simple technology of heatless dryers divert a portion of dried compressed air to an off-line tower. The dry air then flows through and regenerates desiccant. Although operating costs run higher than the heated desiccant dryers, the HL series requires the lowest capital investment.

Features

- **High Quality Air:** Proven high-performance desiccant technology delivers -40°C (-40°F) pressure dew point air for critical applications; pre-filter and after-filter protect desiccant and downstream air from oil contamination and particulates
- **Easy to Maintain:** A low profile design and easy access to components simplifies installation and maintenance
- **Reliable Operation:** High-strength desiccant along with durable valves and components provide extended life
- **Reduced Energy Use:** Low pressure drop design saves on energy costs and provides an economical drying solution
- **Smart Control:** Easy to use, advanced microprocessor helps to maintain dryer performance at optimum levels, while constantly monitoring functions and provides maintenance alerts as well as protection notifications



Model Specifications

Model	Capacity m ³ /min (scfm)	Length x Width x Height mm (in)	Weight kg (lb)	Connection Air In/ Out
HL90	2.5 (90)	762 (30.0) x 1,029 (40.5) x 1,603 (63.1)	215 (475)	1" NPT
HL120	3.4 (120)	762 (30.0) x 1,029 (40.5) x 1,603 (63.1)	255 (563)	1" NPT
HL160	4.5 (160)	813 (32.0) x 1,130 (44.5) x 1,679 (66.1)	321 (707)	1 1/2" NPT
HL200	5.7 (200)	813 (32.0) x 1,130 (44.5) x 1,679 (66.1)	332 (731)	1 1/2" NPT
HL250	7.1 (250)	813 (32.0) x 1,232 (48.5) x 1,697 (66.8)	394 (869)	1 1/2" NPT
HL300	8.5 (300)	813 (32.0) x 1,232 (48.5) x 1,697 (66.8)	419 (924)	2" NPT
HL400	11.3 (400)	919 (36.2) x 1,334 (52.5) x 1,722 (67.8)	506 (1,115)	2" NPT
HL500	14.2 (500)	1,008 (39.7) x 1,435 (56.5) x 2,096 (82.5)	709 (1,564)	2" NPT
HL600	17.0 (600)	1,078 (42.4) x 1,435 (56.5) x 2,096 (82.5)	755 (1,664)	2" NPT
HL800	22.7 (800)	1,302 (51.3) x 1,626 (64.0) x 2,226 (87.6)	915 (2,017)	3" NPT
HL1000	28.3 (1,000)	1,302 (51.3) x 1,626 (64.0) x 2,226 (87.6)	1,015 (2,237)	3" NPT
HL1200	34.0 (1,200)	1,302 (51.3) x 1,626 (64.0) x 2,226 (87.6)	1,100 (2,424)	3" NPT
HL1500	42.5 (1,500)	1,391 (54.8) x 1,981 (78.0) x 2,032 (80.0)	1,349 (2,974)	4" FLG
HL1800	51.0 (1,800)	1,540 (60.6) x 2,134 (84.0) x 2,334 (91.9)	1,771 (3,905)	4" FLG
HL2100	59.5 (2,100)	1,540 (60.6) x 2,134 (84.0) x 2,334 (91.9)	1,941 (4,279)	4" FLG
HL2700	76.4 (2,700)	1,550 (60.8) x 2,134 (84.0) x 2,334 (91.9)	2,234 (4,926)	4" FLG
HL3300	93.4 (3,300)	1,676 (66.0) x 2,440 (96.0) x 2,540 (100.0)	1,338 (2,950)	6" FLG
HL4000	113.3 (4,000)	1,676 (66.0) x 2,440 (96.0) x 2,540 (100.0)	1,361 (3,000)	6" FLG
HL5000	141.6 (5,000)	1,830 (72.0) x 2,590 (102.0) x 2,337 (92.0)	1,792 (3,950)	6" FLG



About Ingersoll Rand Inc. Ingersoll Rand Inc. (NYSE:IR) driven by an entrepreneurial spirit and ownership mindset, is dedicated to helping make life better for our employees, customers and communities. Customers lean on us for our technology-driven excellence in mission-critical flow creation and industrial solutions across 40+ respected brands where our products and services excel in the most complex and harsh conditions. Our employees develop customers for life through their daily commitment to expertise, productivity and efficiency. For more information, visit www.IRCO.com.